

1. A structure for use in a semiconductor package, said structure comprising:

a first adhesive material provided between a die and a circuit board, said first adhesive material in parallel to a length of a wirebond slot in said circuit board, said first adhesive material residing on a first side of said wirebond slot;

a second adhesive material provided between said die and said circuit board, said second adhesive material in parallel to said length of said wirebond slot in said circuit board; said second adhesive material residing on a second side of said wirebond slot; and

a third material provided on said circuit board and extending between said first and second materials to form a diversion dam for an encapsulation material.

2. The structure of claim 1, where said first material is an adhesive tape.

3. The structure of claim 2, where said adhesive tape is a double sided adhesive tape.

4. The structure of claim 1, where said second material is an adhesive tape.

5. The structure of claim 4, where said adhesive tape is a double sided adhesive tape.

6. The structure of claim 1, where said third material is an adhesive tape.

7. The structure of claim 6, where said adhesive tape is a single sided adhesive tape.

5 8. The structure of claim 1, wherein said third material is a thin layer of material applied to one or both of said die and said circuit board, at a location adapted to face an inlet for an encapsulation compound.

9. The structure of claim 1, wherein said third material resides on said die.

10 10. The structure of claim 1, wherein said third material resides on said circuit board.

11. The structure of claim 1, wherein said die is a memory die.

12. A processor system comprising:

a memory; and

15 a processor coupled to said memory, at least one of said processor and said memory being in the form of a die which is coupled to a circuit board by an adhesive system, said adhesive system comprising:

a first adhesive material provided between said die and said circuit board, said first adhesive material being in parallel to a length of a

wirebond slot in said circuit board, said first adhesive material residing on a first side of said wirebond slot;

a second adhesive material provided between said die and said circuit board, said second adhesive material being in parallel to said length of said wirebond slot in said circuit board; said second adhesive material residing on a second side of said wirebond slot; and

a third material provided on said circuit board and extending between said first and second materials to form a diversion dam for an encapsulation material.

10           13.    The system of claim 12, where said first material is an adhesive tape.

14.    The system of claim 13, where said adhesive tape is a double sided adhesive tape.

15           15.    The system of claim 12, where said second material is an adhesive tape.

16.    The system of claim 15, where said adhesive tape is a double sided adhesive tape.

17.    The system of claim 12, where said third material is an adhesive tape.

20           18.    The system of claim 17, where said adhesive tape is a single sided adhesive tape.

19. The system of claim 12, wherein said third material is a thin layer of material applied to one or both of said die and said circuit board at a location adapted to face an inlet for an encapsulation compound.

20. The system of claim 12, wherein said third material resides on said die.

21. The system of claim 12, wherein said third material resides on said circuit board.

22. The system of claim 12, wherein said die is a memory die.

23. A die mounting structure comprising:

a die;

a circuit board containing a wirebond slot;

a first piece of double side adhesive tape secured between said die and said circuit board, said first piece of tape being parallel to a length of said wirebond slot, said first piece of tape residing on a first side of said wirebond slot;

a second piece of double side adhesive tape secured between said die and said circuit board, said second piece of tape being parallel to said length of said wirebond slot in said circuit board; said second piece of tape residing on a second of said wirebond slot; and

a third piece of tape perpendicular to said first and second pieces of doubled sided tape, said third piece of tape contacting said first and second pieces of doubled sided tape to form an encapsulated diversion dam.

5           24.    The structure of claim 23, where said third piece of tape is a single sided adhesive tape.

          25.    The structure of claim 23, wherein said third piece of tape is provided at a location adapted to face an inlet for an encapsulation compound.

10           26.    The structure of claim 23, wherein said third piece of tape resides on said die.

          27.    The structure of claim 23, wherein said third piece of tape resides on said circuit board.

          28.    The structure of claim 23, wherein said die includes a memory device.

15           29.    The structure of claim 23, wherein said die includes a processor.

          30.    A die mounting structure comprising:

                  a die;

                  a circuit board containing a wirebond slot;

a first piece of double side adhesive tape secured between said die and said circuit board, said first piece of tape being parallel to a length of said wirebond slot, said first piece of tape residing on a first side of said wirebond slot;

5 a second piece of double side adhesive tape secured between said die and said circuit board, said second piece of tape being parallel to said length of said wirebond slot in said circuit board; said second piece of tape residing on a second of said wirebond slot; and

10 a thin layer of material provided between said first and second pieces of doubled sided adhesive tape to form an encapsulation diversion dam.

31. The structure of claim 30, where said thin layer of material is at a location adapted to face an inlet for an encapsulation compound.

15 32. The structure of claim 31, wherein said thin layer of material resides on said die.

33. The structure of claim 31, wherein said thin layer of material resides on said circuit board.

34. The structure of claim 31, wherein said die includes a memory device.

20 35. The structure of claim 31, wherein said die includes a processor.

36. A method of encapsulating a semiconductor package, said method comprising:

securing a first adhesive material between a die and a circuit board, said first adhesive material extending in parallel to a length of a wirebond slot in said circuit board, said first adhesive material residing on a first side of said wirebond slot;

securing a second adhesive material between said die and said circuit board, said first adhesive material extending in parallel to said length of said wirebond slot in said circuit board, said first adhesive material residing on a second side of said wirebond slot;

securing a third material between said die and said circuit board and extending between said first and second adhesive materials; and

injecting a compound into a gate, said compound being directed by said third material to fill said wirebond slot last.

37. The method of claim 32 wherein said step of securing said third material comprises securing said third piece of tape on said die.

38. The method of claim 32 wherein said step of securing said third material comprises securing said third piece of tape on said circuit board.

39. The method of claim 32, wherein said step of securing said third material comprises applying a thin layer of material on said die, said thin

15

20

Sub  
A1

372 14  
 contacting said first and  
 method of claim 32,  
 comprises applying a thin  
 layer of material contact  
 a diversion dam.

5

[illegible]